



LS002G


XGT Cordless Slide Compound Miter Saw (216mm)
Powered by 40V MAX Lithium-Ion Battery

Precise cutting and user's comfort

As Powerful as 216mm AC model - High performance in a compact design
Provides 4,800 RPM for faster and smoother cutting

DXT

Miter Saw featured with Deep and Exact Cutting Technology - for superior cutting performance.



Bevel range of 48° right and left











Pull the carriage back slightly and turn the releasing lever for 48° bevel angle in clockwise direction



Max. cutting capacity

70 x 312mm
(height x width)



Cross Cut	Miter Cut (left & right)	Bevel Cut (left & right)	Compound Cut
 	 	 	 
70 x 312mm	Miter 45° left / right	70 x 220mm	Bevel 45° left Miter 45° left / right
			50 x 220mm
		Bevel 45° right	30 x 312mm
			30 x 220mm
			Bevel 45° right Miter 45° left / right

Auto-start Wireless System

Automatically activates compatible AWS vacuum or receiver once the trigger switch is engaged. Paired extraction unit will operate when the saw is in operation and shut down once the trigger is released



Alternatively the vacuum cleaner can be started by pressing button on miter saw

Convenient cleaning the workspace or tool after work.



Note: Wireless unit is required to activate the Bluetooth Part #: 198900-7 (Optional)




LED light casts a shadow of the saw blade onto the work material. The shadow displays the exact thickness of the saw blade allowing the user to make an exact cut.

Dual dust collection ports for efficient dust extraction





Rail-forward design

Using the appreciated mechanism of "Dual dust collection ports"



Extendable sub tables help stabilize long material cuts




550mm
750mm
Width of the turn base

Easy locking and release of bevel angle

Bevel angle can be locked/released by turning the dial behind the front grip, which is located near operator



Positive stop function can be disabled simply by depressing a lever



Specification

Blade Diameter 216 mm

Miter Angle 60° L / 60° R

Bevel Angle 48° L / 48° R

Max Cutting Capacity 90° Miter: 70 x 312 mm

No Load Speed (RPM) 4,800

Sound Pressure / Power Level 89 dB(A) / 100 dB(A)

Dimensions (L x W x H) 702 x 551 x 557 mm

Net weight 15.2 kg (without battery)

Available Variants

VARIANTS	MODELS	BATTERY	CHARGER	MAKPAC STACKING CASE
BARE TOOL	LS002G Z	-	-	-

Accessories

TCT Effiicut Saw Blade (Optional)

	Dia (mm)	Material	No. of teeth	Kerf (mm)	Plate	Rake	Tooth shape	Bore (mm)	Part No.
	216	Wood	45	2	1.5	10	ATBR	25.4	E-07010
NEW	216	Wood	60	2	1.5	10	ATBR	25.4	E-08969
	216	Wood	80	2	1.5	10	ATBR	25.4	E-08975

Horizontal vise
122567-9
(standard)



Triangular Rule
762001-3
(standard)



Dust bag
127512-9
(standard)



Makita

MAKITA GULF FZE

www.makita.ae

